


TKS-104c-MODUL



FEATURES

- Panel mount version with reverse side threaded bolts
- Excellent tactile feedback
- Key relief printing
- Chemical, abrasion and scratch resistant frontsheet
- Resistant against dirt, dust and liquids (IP65)

TECHNICAL DATA


Number of keys:	104	Interfaces:	PS/2; USB
Mounting type:	front panel with threaded bolts	USB compatibility:	complies with USB 2.0
Front panel material:	aluminium	Operating temperature:	-25 °C to +70 °C
Keyswitch technology:	short travel keys	Storage temperature:	-25 °C to +80 °C
Switching cycles:	approx. 3 mill. (per key)	Dimensions:	370 x 180 x 26.3mm
Operating force:	2.6 N	Weight:	1000 g
Switch travel:	0.3 mm		
Protection level (max):	IP65 (front)		

Cat.No.	Product description	Interface	Layout
KS18288	TKS-104c-MODUL-USB-DE	USB	German
KS18289	TKS-104c-MODUL-USB-US	USB	US
KS18286	TKS-104c-MODUL-PS/2-DE	PS/2	German
KS18287	TKS-104c-MODUL-PS/2-US	PS/2	US

Other language versions / interfaces / configurations available on request.

Subject to modifications and errors

TECHNICAL DRAWING (in mm)



Subject to modifications and errors

GETT Gerätetechnik GmbH

Mittlerer Ring 1 | 08233 Treuen | Germany
Tel: +49 37468 660-0
Fax: +49 37468 660-66
E-Mail: info@gett.de
Internet: www.gett.de

Gett North America LLC

E-Mail: info@gett-na.com
Internet: www.gett-na.com

Gett Asia Ltd.

E-Mail: info@gett-asia.com
Internet: www.gett-asia.com

gett.de
gett-group.com