


TKS-105c-TB38-FP-4HE



FEATURES

- Designed for 19" rack
- Excellent tactile feedback
- Key relief printing
- Integrated 38-mm trackball
- Chemical, abrasion and scratch resistant frontsheet
- Resistant against dirt, dust and liquids (IP65)

TECHNICAL DATA

Number of keys:	105	Operating temperature:	0 °C to +70 °C
Mounting type:	19-inch-front panel with mounting holes	Storage temperature:	-25 °C to +80 °C
Front panel material:	aluminium	Dimensions:	482.6 x 177.8 (4HE) x 61.6 mm
Keyswitch technology:	short travel keys	Weight:	1300 g
Switching cycles:	approx. 3 mill. (per key)		
Operating force:	2.6 N		
Switch travel:	0.3 mm		
Protection level:	IP65 static, IP54 dynamic		
Interfaces:	PS/2; USB		
USB compatibility:	USB V1.1 compliance		

TECHNICAL DATA TRACKBALL


Ball diameter:	38 mm
Ball material:	phenolic resin
Operating principle:	mechanical

Cat.No.	Product description	Interface	Layout
KS18328	TKS-105c-TB38-FP-4HE-USB-DE	USB	German
KS18329	TKS-105c-TB38-FP-4HE-USB-US	USB	US
KS18326	TKS-105c-TB38-FP-4HE-PS/2-DE	PS/2	German
KS18327	TKS-105c-TB38-FP-4HE-PS/2-US	PS/2	US

Other language versions/interfaces/configurations available on request.

Subject to modifications and errors

TECHNICAL DRAWING (in mm)



Subject to modifications and errors